

FLUIDE AT 42



AUTOMATIC TRANSMISSION FLUID

USES

- Automatic or semi-automatic transmissions and torque converters of passenger cars, light commercial vehicles and industrial vehicles, when the manufacturer requires an ATF (Automatic Transmission Fluid) GM DEXRON® - III.
- Suitable for use in transmissions of trucks, buses and public works machineries when a fluid type ALLISON C4 is required.
- Hydraulic systems when a fluid type GM DEXRON® - III is required.

PROPERTIES

- Very high viscosity index linked with an excellent viscosity stability in operation.
- Very low pour point.
- Very good thermal stability.
- Excellent resistance to oxidation.

CHARACTERISTICS

FLUIDE AT 42	Unit	
Volumetric mass at 15°C	kg/m ³	860
Colour	-	Red
Viscosity at 40°C	mm ² /s	34
Viscosity at 100°C	mm ² /s	7.7
Viscosity index	-	207
Viscosity Brookfield at -40°C	mPa.s	13 300
Flash point Cleveland	°C	196
Pour point	°C	-51

The typical characteristics mentioned represent mean values.

PERFORMANCES

ALLISON C4 n° C4-24842997
BMW group 24 - 3.0
FORD MERCON® (92) n° M970909
DEXRON® - III n° G-34196
MAN 339 type F

PSA PEUGEOT CITROEN (ZF 4HP14 & ZF 4HP18)
VOITH 55.6335.32
ZF TE-ML 04D, 09B, 17C
MERCEDES BENZ 236.1 and 236.5
NISSAN

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

FLUIDE AT 42
JULY 2005
N° MPR 07/05



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard. A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant