

CIRKAN ZS



Lubrication



High performance machine oils.

APPLICATIONS

Oil for moving parts

- **CIRKAN ZS** oils are mineral oils containing additives with appropriate viscosities for lubricating moving parts operating in severe conditions of temperature and load:
 - precision machinery
 - reduction drives and variators not requiring an EP oil
 - machinery lubricated by oil mist not requiring EP additives
 - loss lubrication of moving parts requiring an anti-wear oil.

SPECIFICATIONS

International specifications

- ISO 6743/6 CKB
- ISO 12925-1 cat.CKB

ADVANTAGES

- High natural viscosity number
- Good seals compatibility
- Very good anti-wear properties
- Excellent anti-foaming, anti-corrosion and anti-oxidation properties.

TYPICAL CHARACTERISTICS	METHODS	UNITS	CIRKAN ZS	
			220	320
Density at 15 °C	ISO 3675	kg/m ³	900	905
Viscosity at 40 °C	ISO 3104	mm ² /s	220	320
Viscosity index	ISO 2909		96	96
Pour point	ISO 2592	°C	- 9	- 9
Open cup flash point	ISO 3016	°C	260	270

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS

Industrie & Spécialités

22 october 2002 (supersedes 7 june 2001)

CIRKAN ZS

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

